

# MULTICUT 300

The no compromise mower for the most demanding of vegetation management tasks. The MULTICUT 300 is shaft driven and features the HD2 blade system for maximum lifting and cutting capacity. Specially designed under deck construction contributes to a thorough chopping of the crop and an even spread from the rear of the machine leaving a finish to be proud of.

- 3.0 metre Cutting Width
- High Strength Steel Deck Construction
- Replaceable Full Length Skids
- 161HP Input Splitter Gearbox
- Heavy Duty 111HP Rotor Gearboxes
- Front & Rear Chain Safety Curtains
- 8 PLY—500 x 8 Industrial Tyres
- HD2 High Lift Blade Kit
- Anti Scalp Rotor Protection Dishes
- 140MM Blade Overlap for Clean Cutting
- Input Knocking Clutch for Tractor Protection
- Shock Absorber Driveline Protection
- Rapid in Field Cutting Height Adjustment
- Floating Linkage

MODEL	MULTICUT 300
Cutting Width	2.85m
Overall Width	3.00m
Machine Weight	1050kg
Transport Width	3.00m
Gearbox Rating	161hp & 111hp
Cutting Range	10-350mm
Number of Rotors	2
Blades	4
PTO Protection	Knocking Clutch & Rubber Shock Absorber
PTO Speed	1000rpm
Tractor Power Required	50hp

