

Herd

MODEL I-92



2" RECEIVER HITCH MOUNT I-92 ELECTRIC

I-92 Seeder for spreading seeds, insecticides and herbicides. (PTO-powered units recommended for spreading fertilizer.)

Can be purchased with 2" receiver hitch mount, front mount, or side mount. Ideal for front of tractor, pickup, Jeeps, etc., as all you need is 12 volts to run the seeder.

I-92 comes with an agitator to give Herd's Sure-Feed of material through the opening. You can also center the spread and meter the amounts with Herd's centering and opening control design (now stainless steel).

Also available: a smaller 44 qt. with all the features of the I-92 only smaller.

OPTIONAL EQUIPMENT:

813 Rheostat

982 Hopper Ext. for I-92 w/2 Bu. Cap

808A Width-Control Kit

660 2" Receiver Hitch Mount only

See Specification Chart on Page 8 for more information.



**FRONT-MOUNTED
MODEL I-92 ELECTRIC**



GT-77 now with hitches for your favorite ATV. Specify make and size ATV when ordering GT-77.



SIDE-MOUNTED ORCHARD-TYPE ELECTRIC I-92, 92 Qt. Capacity

The Model I-92 Orchard, side mounted, standard with front chute 822 and spout 827 and 808A Width Control Kit is deal for spreading granular insecticides, mouse bait, or herbicides, as CASORON, around trees and under link fences. Rheostat is used to regulate depth of spread. The smaller I-44 can be identically equipped.

These units are perfectly suited for spreading granular herbicides for grass or weed control around airports, along highways, on ditch banks and anyplace where you wish to control weeds or grass. Herd's easy on-and-off control makes quick work of 'spot' weed control in highway plantings and nurseries. May be used on boats or pickups for side spreading.

Some granular chemicals, as CASORON and the like, may be spread in winter ahead of busy spring work.

Herd

MODEL GT-77



MODEL GT-77 ELECTRIC, 77 LB. CAPACITY

THE HOME OWNER'S BROADCASTER...BUILT TO SPREAD ALL SEEDS, FERTILIZER, GRANULAR INSECTICIDES AND HERBICIDES...DOING IT FAST AND EFFICIENTLY.

This GT-77 broadcaster comes standard equipped with 12 Volt motor, Rheostat for width control, Wiring Harness with Fuse and Quick-Coupler, Pivot Plate to center spread, and stainless steel parts where it counts. Lid keeps the weather out and your material dry.

OPTIONAL EQUIPMENT:

Blocking Plate 517 for spreading small amounts.

3-pt. Mounting Frame 521 for Category "0" garden tractors.

See Specification Chart on Page 8 for more information.

AVERAGE WIDTHS OF SPREADS FOR THE FOLLOWING MATERIALS

	Model M-96 3-pt. Standard	Model F-160 3-pt. Standard	Model I-92 I-44	Model 2440 1200C 7500	Model M-96 3-pt. Standard	Model F-160 3-pt. Standard	Model I-92 I-44	Model 2440 1200C 7500	
Alfalfa	18'	18'	26'	28'	24'	24'	26'	33'	
Ammonium Nitrate	18'	20'	20'	28'-36'	12'	12'	16'	12'	
Australian Pea	28'	30'	34'	40'	12'	12'	18'	18'	
Blue Grass	12'	12'	18'	18'	24'	24'	30'	33'	
Brome Grass	12'	12'	14'	10'	26'	26'	32'	34'	
Clover	18'	18'	28'	28'	14'	14'	21'	18'	
Fertilizer	18'	18'	24'	28'-36'	36'	36'	36'	40'	
Flax and Millet	20'	22'	30'	30'	18'	18'	28'	32'	
Herbicides	Not recommended	5'-22'	22'		16'	16'	24'	24'	
Insecticides	Not recommended	5'-22'	22'		24'	24'	36'	40'	
Ladino Clover	18'	18'	28'	28'	26'	26'	36'	40'	
Lespedeza	18'	18'	28'	30'	26'	26'	32'	34'	
Oats					184 lb. or 3-12 cu. ft. or 2-7/8 bu.	184 lb. or 3-12 cu. ft. or 2-7/8 bu.	88 lb. or 1.6 cu. ft. or 1-3/8 bu.	88 lb. or 1.6 cu. ft. or 1-3/8 bu.	77 lb. or 1.4 cu. ft. or 1-1/5 bu.
Orchard Grass									
Red Top									
Rice									
Rye									
Rye Grass									
Soybeans									
Sweet Sudan Grass									
Timothy									
Turnip Seed									
Vetch									
Wheat									

SPECIFICATIONS

MODEL NUMBER:	2440, 3-pt. REGULAR & ORCHARD	1200C, 3-pt. REGULAR & ORCHARD	750, 3-pt. REGULAR & ORCHARD	F-160, 3-pt	F-160, Standard Drawbar	M-96, 3-pt.	M-96 Standard Drawbar	I-92, Electric Farm-Type	I-92, Electric Orchard-Type	I-44, Electric Farm-Type	I-44, Electric Orchard-Type	GF77 Electric
HOPPER CAPACITY	2440 lb., or 40 cu. ft. or 32 bu.	1200 lb., or 20 cu. ft. or 16 bu.	750 lb., or 12 cu. ft. or 9.6 bu.	320 lb., or 6-1/4 cu. ft. or 5 bu.	320 lb., or 6-1/4 cu. ft. or 5 bu.	192 lb., or 3-3/4 cu. ft. or 3 bu.	192 lb., or 3-3/4 cu. ft. or 3 bu.	184 lb., or 3-12 cu. ft. or 2-7/8 bu.	184 lb., or 3-12 cu. ft. or 2-7/8 bu.	88 lb., or 1.6 cu. ft. or 1-3/8 bu.	88 lb., or 1.6 cu. ft. or 1-3/8 bu.	77 lb., or 1.4 cu. ft. or 1-1/5 bu.
Hopper Extension-Optional		800 lb. capacity 11-1/2" high	None available	3 bu. capacity 18" high, round 3-3/4 cu. ft. For light-weight material only.	3 bu. capacity 18" high, round 3-3/4 cu. ft. For light-weight material only.	2 bu. capacity 18" high, round 2-1/2 cu. ft. For light-weight material only.	2 bu. capacity 18" high, round 2-1/2 cu. ft. For light-weight material only.	2 bu. capacity 18" high, round 2-1/2 cu. ft. For light-weight material only.	2 bu. capacity 18" high, round 2-1/2 cu. ft. For light-weight material only.	1.3 bu. capacity 18" high, round 1.6 cu. ft. For light-weight material only.	1.3 bu. capacity 18" high, round 1.6 cu. ft. For light-weight material only.	None
Shipping Wt.	525 lb.	315 lb.	215 lb.	145 lb. (3-pt.)	128 lb.	80 lb.	74 lb.	86 lb.	80 lb.	75 lb.	70 lb.	49 lb.
Outside Dimensions	40"x60"x 65-1/2" high	31"x43"x 53" high	22"x36"x 49" high	26-1/2" across top of hopper, 40" high, 31" front to back, 32" hitch.	26-1/2" across top of hopper, 40" high, 31" front to back.	20" across top of hopper, 36" high, 24" front to back, 32" hitch.	20" across top of hopper, 36" high, 24" front to back.	21" across top of hopper, 40" high, 29-1/2" front to back, 21" wide.	21" across top of hopper, 40" high, 29-1/2" front to back, 21" wide.	15-1/2" across top of hopper, 30" high, 21" front to back, 15-1/2" wide.	15-1/2" across top of hopper, 30" high, 21" front to back, 15-1/2" wide.	15-1/2" across top of hopper, 25" high, 21" front to back, 15-1/2" wide.
Trailers	70" wide from rim edge to rim edge, 58-1/2" long.											
COVERAGE	Up to 40 A. Per Hour	Up to 40 A. Per Hour	Up to 40 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour	Up to 25 A. Per Hour
Amount per Acre	3 lbs. to 1,000 lbs.	3 lbs. to 1,000 lbs.	3 lbs. to 1,000 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	2 lbs. to 500 lbs.	1/2 lb. 500 sq. ft. to 500 lbs. per A.
Feed Opening	All-Adjustable in Thousandths of an Inch											
Opening Control	Remote hydraulic control	Handle (Optional-Remote hydraulic)	Handle (Optional-Remote hydraulic)	Upper and lower handles	Upper and lower handles	Upper and lower handles	Upper and lower handles	Lower Pulley for remote control	Lower Pulley for remote control	Lower Pulley for remote control	Lower Pulley for remote control	Low-In line with seal
Pivot Plate for Centering Spread	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes-Stainless Steel
Agilator in Hopper	Yes-Rotates. Is removable. Special one available for dehydrated lime.	Yes-Rotates. Is removable. Special one available for dehydrated lime.	Yes-Rotates. Is removable. Special one available for dehydrated lime.	Yes-Rotates.	Yes-Rotates.	Yes-Rotates.	Yes-Rotates.	Yes-Rotates. Is removable.	Yes-Rotates. Is removable.	Yes-Rotates. Is removable.	Yes-Rotates. Is removable.	Yes-Vibrating
Fan	Aluminum Base, with 4 replaceable steel blades.	Aluminum Base, with 4 replaceable steel blades.	Aluminum Base, with 4 replaceable steel blades.	6-Bladed Aluminum Corrosive-resistant	6-Bladed Aluminum Corrosive-resistant	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.	4-Bladed Lapover Aluminum Corrosive-resistant.
Hopper Base Plate	One-piece Aluminum	One-piece Aluminum	One-piece Aluminum	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron	One-piece Grey-iron
HOPPER	14 Ga. Steel, Rectangular, Welded Seams	14 Ga. Steel, Rectangular, Welded Seams	14 Ga. Steel, Rectangular, Welded Seams	22 Gauge Galvanize-Round	22 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round	24 Gauge Galvanize-Round
Lid	Optional	Optional Lid for H.E.	Optional	None	None	Lid & Spring-Optional	Lid & Spring-Optional	Lid & Spring-included.	Lid & Spring-included.	Lid & Spring-included.	Lid & Spring-included.	Lid & Spring-included.
Carrying Frame	Built-in Unit of 3"x2" & 2"x2" Heavy-walled Tubing.	Built in Unit of 2" Sq. Tubing. Doubled where needed.	Built-in Unit of 2" Sq. Tubing.	Heavy-duty separate frame for 3-pt.	Heavy-duty adjustable stand with belt tightener.	Sturdy 3-pt. Frame	Sturdy twin-stand with vertical adjustment for belt tightener.	L-Arms for front mounting. Cross-angle for rear.	Heavy-duty bracket for side-mounting.	L-Arms for front mounting. Cross-angle for rear.	Heavy-duty bracket for side-mounting.	1 piece stand
Bracing	Built-in	Built-in	Built-in	2 Used with 3-pt. Frame	2 Sets.	Built-in.	2 Sets.	1 Set	None used (Side mounted)	1 Set	None used (Side mounted)	1 Set, with U-Bolts for Axle
Mounting	On All Category 2 tractors with 3-pt. Hitch. Also for Quick-Hitch.	On All Category 2 tractors with 3-pt. Hitch. Optional: Cat. 1 Kit.	All tractors with Category 1 3-pt. Hitch. Optional: Cat. 2 Kit.	Tractors with Category 1, 3-pt.	All popular makes tractors. Adjustable for short or long drawbar.	Tractors with 3-pt. Category 1	All popular makes tractors. Adjustable for short or long drawbar.	All tractors with 12 volt system.	Side-mounting frame fits most tractors. 12 volt system required.	All tractors with 12 volt system.	Side-mounting frame fits most tractors. 12 Volt system required.	All garden tractors with 12 volt systems. Category 0, 3-pt. hitch available.
Powered by	Quik-Tach shielded telescoping P.T.O. shaft.	Quik-Tach Shielded telescoping P.T.O. shaft.	Quik-Tach shielded telescoping P.T.O. shaft.	Quik-Tach Shielded telescoping P.T.O. shaft.	V-Belt, from 2-speed pulley on P.T.O.	Quik-Tach shielded telescoping P.T.O. shaft.	V-Belt, from 2-speed pulley on P.T.O.	Electric Motor 12 volt DC. 24 volt optional.	Electric Motor 12 volt DC. 24 volt optional.	Electric Motor 12 volt DC. 24 volt optional.	Electric Motor 12 volt DC. 24 volt optional.	Electric Motor 12 volts.
Bearings	Tapered bearings in enclosed gearbox.	Tapered bearings in enclosed gearbox.	Tapered bearings in enclosed gearbox.	Bronze bearings, with grease fittings. Sealed bearing in hopper.	Bronze bearings, with grease fittings. Sealed bearing in hopper.	Bronze bearings, with grease fittings.	Bronze bearings, with grease fittings.	Oilite bronze and sealed bearing.	Oilite bronze and sealed bearing.	Oilite bronze and sealed bearing.	Oilite bronze and sealed bearing.	Oilite bronze
Gears	Drop-forged, step-up, run-in-oil, in enclosed gearbox. For 540 rpm, reversible for 1,000 rpm.	Drop-forged, step-up, run-in-oil, in enclosed gearbox. For 540 rpm, reversible for 1,000 rpm.	Drop-forged, step-up, run-in-oil, in enclosed gearbox. For 540 rpm, reversible for 1,000 rpm.	Heavy-duty Mtre with Half-Moon Keys-shielded.	Heavy-duty Mtre with Half-Moon Keys-shielded.	Special Mag-Bronze Step-up for 540 rpm, with Half-Moon Keys-shielded.	Gray-iron, milre-shielded.	Direct drive.	Direct drive.	Direct drive.	Direct drive.	Direct drive.
Optional and/or Furnished Equipment	Optional: 158 Lime Agilator; 268 & 1035 Reg. Ttr.; 269 & 1035 Or. Ttr.; 225 Hy. Con. Band. Kit; 838 Hy. Con. Side-Pat. Kit; 1090 Sm. Seed Hopper.	Optional: 158 Lime Agilator; 268 & 266 Reg. Ttr.; 269 & 266 Or. Ttr.; 82 Man. Side-Pat. Con. Kit; 180 Man. Band. Kit; 1090 Sm. Seed Hopper; 1000 Remote Hy. Con. Kit; 838 Hy. Con. Side-Pat. Kit (used w/1000 Kit); 225 Hy. Con. Band. Kit (used w/1000 Kit); 525 Dual Con. for 225 Kit; Reg. Ttr. 268 & 844; Or. Ttr. 269 & 844.	158 Lime Agilator; 82 Man. Side-Pat. Con. Kit; 180 Man. Band. Kit; 1090 Sm. Seed Hopper; 1000 Remote Hy. Con. Kit; 838 Hy. Con. Side-Pat. Kit (used w/1000 Kit); 225 Hy. Con. Band. Kit (used w/1000 Kit); 525 Dual Con. for 225 Kit.					Optional: 808 Kit 808A Kit 813 Rheostat	Included: 808A Kit 822 Front Chute 827 Spout Kit	Optional: 808 Kit 808A Kit 813 Rheostat	Included: 808A Kit 822 Front Chute 827 Spout Kit	517 Blocking Plate; 521 3-pt. Mfg. Frame for Cat. 10" garden tractors; Special hitches for ATVs.



SEEDER CO., INC.

2383 South U.S. 35, P.O. Box 448

Logansport, Indiana 46947-0448

Phone: 574-753-6311 / Fax: 574-722-4106

www.herdseeder.com