



ROUNDUP AL

ALL ALUMINUM GOOSENECK STOCK TRAILER.

AVAILABLE SIZES

- 16' X 6'8" X 6'6" w/2-5200# axles, 15" tires & 6-hole wheels
- 20' X 6'8" X 6'6" w/2-6000# axles, 16" tires & 8-hole wheels
- 24' X 6'8" X 6'6" w/2-7000# axles, 16" tires & 8-hole wheels
- 28' X 6'8" X 6'6" w/2-7000# axles, 16" tires & 8-hole wheels
- 16' X 6'8" X 7' w/2-5200# axles, 15" tires & 6-hole wheels
- 20' X 6'8" X 7' w/2-6000# axles, 16" tires & 8-hole wheels
- 24' X 6'8" X 7' w/2-7000# axles, 16" tires & 8-hole wheels
- 28' X 6'8" X 7' w/2-7000# axles, 16" tires & 8-hole wheels

DIMENSIONS

- 7' gooseneck length
- 6' 6" Tall
- 6' 8" Width

UNDERCARRIAGE

- Rubber torsion axles w/four-wheel independent suspension & greasable hubs
- Forward self adjusting electric brakes on all wheels
- Radial tires on silver modular wheels w/ chrome center caps
- Spare tire rack under gooseneck

COUPLER AND JACKS

- Adjustable stem w/set screw & pin w/ 2-5/16" coupler & safety chains w/hooks
- Emergency breakaway system: switch, cable & battery box compete w/battery & charger
- 12K Single speed drop-leg jack w/ removable jack handle/ lug wrench

DESIGN FEATURES AND HARDWARE

- All aluminum frame w/ 9" extruded side slats & air gaps
- Heavy duty low profile 2"x4 3/16" steel gooseneck structure
- .125 extruded aluminum top rail
- 1 3/8" X 2" wall uprights
- 9" extruded aluminum bottom rail
- One-piece .040 aluminum skin roof w/ 1" x 2-1/2" tubing bows on 2' centers
- Tapered nose w/radius corners
- Plexiglass rails on both sides (plexiglass not standard)
- 12" aluminum plank floor
- Full length aluminum running boards
- Rubber dock bumper below rear door
- Tag bracket
- Colors available white or black aluminum skin

LOAD AREA EQUIPMENT

- Side access 30" door on curb side w/heavy duty cam bar assembly
- Drop down calf gate w/double spring-loaded latch
- Center gate w/hold back & spring loaded slam latch (24' & 28' lengths have 2)
- Interior tie rings (2 in front; 2 at center gate)
- Full swing half sliding rear gate with spring latch, heavy duty cam bar & ball bearing rollers.

LIGHTS AND ELECTRICAL

- DOT approved lighting

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.